

WASTE COMPACTORS

“Waste management equipment for the demanding maritime and offshore industry that gets the job done efficiently, safely and in an environmentally responsible manner.”



**DT-200MC, DT-500MC,
DT-1500MC & DT-2000MC**

KEY BENEFITS

- Stainless steel units for indoor or outdoor placement
- Wheeled, interchangeable stainless steel containers for easy waste segregation and logistics.
- Combined compactor and baler (DT-200MC only).
- Delitek products are certified by DNV.
- Powerful electro/hydraulic drive for high press-force.
- Compaction directly into big bags for easy deployment of waste (HD plastic bags as alternative for DT-200MC).
- Easy installation and operation (Plug & Play).
- EX-versions with DNV unit certification available.

**MARINE****OFFSHORE****NAVY****CRUISE****YACHT****FISHING****ONSHORE****DT-200MC**

Material	Stainless steel AISI 304, AISI 316 or painted steel
Capacity	0,2 m ³
Loading opening (W x H)	600mm x 400mm
Compaction force	9 tons
Dimensions (W x D x H)	680mm x 705mm x 1958mm
Weight (Incl. container)	199 Kg
Motor voltage	220V / 380~440V / 480V / 690V, 3Ph, 50~60Hz
Motor power	<1,8 kW
Alternative power supply	Pneumatic/Hydraulic or Pneumatic only
Noise level	<65dB Max

DT-500MC

Material	Stainless steel AISI 304 or AISI 316
Capacity	0,5 m ³
Loading opening (W x H)	720mm x 400mm
Compaction force	10 tons
Dimensions (W x D x H)	1016mm x 967mm x 2276mm
Weight (Incl. container)	312 Kg
Motor voltage	220V / 380~440V / 480V / 690V, 3Ph, 50~60Hz
Motor power	<1,8 kW
Alternative power supply	Pneumatic/Hydraulic
Noise level	<65dB Max

DT-1500MC

Material	Stainless steel AISI 304 or AISI 316
Capacity	1,5 m ³
Loading opening (W x H)	1120mm x 435mm
Compaction force	15 tons
Dimensions (W x D x H)	1586mm x 1203mm x 2821mm
Weight (Incl. container)	582 Kg
Motor voltage	220V / 380~440V / 480V / 690V, 3Ph, 50~60Hz
Motor power	<1,8 kW
Alternative power supply	Pneumatic/Hydraulic
Noise level	<65dB Max

DT-2000MC

Material	Stainless steel AISI 304 or AISI 316
Capacity	2 m ³
Loading opening (W x H)	1500mm x 400mm
Compaction force	15 tons
Dimensions (W x D x H)	1999mm x 1513mm x 2817mm
Weight (Incl. container)	610 Kg
Motor voltage	220V / 380~440V / 480V / 690V, 3Ph, 50~60Hz
Motor power	<1,8 kW
Alternative power supply	Pneumatic/Hydraulic
Noise level	<65dB Max

Delitek AS (Head Office)

Moloveien 1 N-8432 Alsvåg, Norway Tel: +47 76 18 57 60 Fax: +47 76 13 42 77 e-mail: mail@delitek.no
www.delitek.no